Leyland Trade

Technical Data

Satinwood

A hard wearing, knock-resisting, satin finish which is self-undercoating and easy to use on interior wood and metalwork.

Recommended uses

Interior ✓ Exterior ✗

Type of substrate

Wood and metal.

Colour availability

Brilliant White (5ltr, 2.5ltr & 750ml)

Finish

Satin

Volume solid

56%

Coverage

1 litre will cover approximately 20 square metres, depending on the nature and porosity of the surface. Strong or contrasting colours may require additional coats. When using more than one tin of a colour in the same room, intermix before use.

Drying time

Touch dry in 4-6 hours.
Recoatable after 16-24 hours.

Transportation and storage

To avoid the risk of spillage, always store and transport in a secure upright position. Store away from heat and flame.

Film thickness

Wet: 50µm
Dry: 28µm

Preparation

Ensure surface to be painted is sound, clean, dry and free from grease. Remove all loose and defective paint. Prime all new and bare surfaces with the appropriate Leyland Primer. Rub down sound previously painted surfaces with fine waterproof abrasive paper to provide a key. Avoid the inhalation of dust. Wear a suitable face mask if dry sanding. Special precautions should be taken during surface preparation of pre-1960s paint surfaces over wood and metal as they may contain harmful lead. For further advice contact Technical Advisory.

Application

Stir well before use. Apply evenly by brush or roller and avoid overspreading. Apply one or more coats as required and allow 16-24 hours drying between coats under normal conditions. Do not apply over polystyrene surfaces.

Cleaning

Remove as much product as possible from application equipment before cleaning. Clean equipment immediately after use with White Spirit or Turpentine Substitute. Some local authorities have special facilities for disposal of waste coatings. Do not empty product into drains or watercourses. Replace lid firmly.

Warning

- Keep out of reach of children.
- Avoid contact with skin and eyes.
- Do not ingest.
- If medical advice is needed have container or label to hand.
- Please refer to Product Label & Safety Data Sheet (SDS) for hazard warnings and information on safe handling/use/transport/storage/disposal/emergency.
- SDS available: www.leylandtrade.com or call 01924 354354

Whilst we use the latest technology in our paints, the nature of solvent based trim products means that they have the potential to yellow over time, when exposed to certain conditions. For a finish that stays whiter for longer, please use Leyland Trade Fast Drying Satin.